

CG cores

| Number      | Cores    | a <sub>max</sub><br>mm | b-1 pt<br>mm | f<br>mm | c<br>mm  | g <sub>min</sub><br>mm | e <sub>min</sub><br>mm | r <sub>max</sub><br>mm | m <sub>Fe</sub><br>kg | l <sub>Fe1</sub><br>cm | A <sub>Fe</sub><br>cm <sup>2</sup> | P <sub>n</sub><br>VA |
|-------------|----------|------------------------|--------------|---------|----------|------------------------|------------------------|------------------------|-----------------------|------------------------|------------------------------------|----------------------|
| 7,00125E+11 | CG27/6   | 29.4                   | 21.0         | 7.2     | 7.2-0.8  | 6.4                    | 14.3                   | 1.0                    | 0.018                 | 6.3                    | 0.37                               |                      |
| 7,00125E+11 | CG33/8   | 35.7                   | 25.8         | 8.7     | 8.7-0.8  | 7.9                    | 17.5                   | 1.0                    | 0.035                 | 7.8                    | 0.58                               |                      |
| 7,00125E+11 | CG41/9   | 43.7                   | 30.6         | 10.3    | 10.3-0.8 | 9.5                    | 22.2                   | 1.0                    | 0.063                 | 9.5                    | 0.86                               |                      |
| 7,00125E+11 | CG48/9   | 50.0                   | 32.1         | 10.3    | 10.3-0.8 | 11.1                   | 28.6                   | 1.0                    | 0.074                 | 11.1                   | 0.86                               |                      |
| 7,00125E+11 | CG54/13  | 56.4                   | 30.6         | 13.5    | 8.7-0.8  | 12.7                   | 38.1                   | 1.5                    | 0.094                 | 12.8                   | 0.96                               | 16                   |
| 7,00125E+11 | CG54/19  | 56.4                   | 30.6         | 19.8    | 8.7-0.8  | 12.7                   | 38.1                   | 1.5                    | 0.141                 | 12.8                   | 1.44                               | 25                   |
| 7,00125E+11 | CG54/25  | 56.4                   | 30.6         | 26.2    | 8.7-0.8  | 12.7                   | 38.1                   | 1.5                    | 0.187                 | 12.8                   | 1.92                               | 34                   |
| 7,00125E+11 | CG54/38  | 56.4                   | 30.6         | 38.9    | 8.7-0.8  | 12.7                   | 38.1                   | 1.5                    | 0.281                 | 12.8                   | 2.88                               | 50                   |
| 7,00125E+11 | CG70/13  | 73.0                   | 36.9         | 13.5    | 10.3-0.8 | 15.9                   | 50.8                   | 1.5                    | 0.145                 | 16.5                   | 1.15                               | 33                   |
| 7,00125E+11 | CG70/13  | 73.0                   | 36.9         | 19.8    | 10.3-0.8 | 15.9                   | 50.8                   | 1.5                    | 0.218                 | 16.5                   | 1.17                               | 51                   |
| 7,00125E+11 | CG70/25  | 73.0                   | 36.9         | 26.2    | 10.3-0.8 | 15.9                   | 50.8                   | 1.5                    | 0.291                 | 16.5                   | 2.30                               | 68                   |
| 7,00125E+11 | CG70/32  | 73.0                   | 36.9         | 32.5    | 10.3-0.8 | 15.9                   | 50.8                   | 1.5                    | 0.363                 | 16.5                   | 2.87                               | 84                   |
| 7,00125E+11 | CG76/19  | 79.4                   | 40.1         | 19.8    | 10.3-0.8 | 19.0                   | 57.2                   | 3.0                    | 0.239                 | 18.1                   | 1.72                               | 65                   |
| 7,00125E+11 | CG76/25  | 79.4                   | 40.1         | 26.2    | 10.3-0.8 | 19.0                   | 57.2                   | 3.0                    | 0.319                 | 18.1                   | 2.30                               | 87                   |
| 7,00125E+11 | CG76/32  | 79.4                   | 40.1         | 32.5    | 10.3-0.8 | 19.0                   | 57.2                   | 3.0                    | 0.398                 | 18.1                   | 2.87                               | 108                  |
| 7,00125E+11 | CG76/38  | 79.4                   | 40.1         | 38.9    | 10.3-0.8 | 19.0                   | 57.2                   | 3.0                    | 0.478                 | 18.1                   | 3.45                               | 128                  |
| 7,00125E+11 | CG89/22  | 92.1                   | 49.6         | 23.0    | 13.5-0.8 | 22.2                   | 63.5                   | 3.0                    | 0.432                 | 21.1                   | 2.68                               | 131                  |
| 7,00125E+11 | CG89/29  | 92.1                   | 49.6         | 29.4    | 13.5-0.8 | 22.2                   | 63.5                   | 3.0                    | 0.553                 | 21.1                   | 3.45                               | 168                  |
| 7,00125E+11 | CG89/38  | 92.1                   | 49.6         | 38.9    | 13.5-0.8 | 22.2                   | 63.5                   | 3.0                    | 0.739                 | 21.1                   | 4.60                               | 219                  |
| 7,00125E+11 | CG89/51  | 92.1                   | 49.6         | 51.6    | 13.5-0.8 | 22.2                   | 63.5                   | 3.0                    | 0.989                 | 21.1                   | 6.13                               | 286                  |
| 7,00125E+11 | CG108/19 | 111.1                  | 62.3         | 19.8    | 16.7-0.8 | 28.6                   | 76.2                   | 3.0                    | 0.567                 | 25.9                   | 2.87                               | 206                  |
| 7,00125E+11 | CG108/29 | 111.1                  | 62.3         | 29.4    | 16.7-0.8 | 28.6                   | 76.2                   | 3.0                    | 0.898                 | 25.9                   | 4.54                               | 319                  |
| 7,00125E+11 | CG108/38 | 111.1                  | 62.3         | 38.9    | 16.7-0.8 | 28.6                   | 76.2                   | 3.0                    | 1.14                  | 25.9                   | 5.75                               | 400                  |
| 7,00125E+11 | CG108/51 | 111.1                  | 62.3         | 51.6    | 16.7-0.8 | 28.6                   | 76.2                   | 3.0                    | 1.52                  | 25.9                   | 7.66                               | 520                  |
| 7,00125E+11 | CG127/25 | 130.2                  | 75.0         | 26.2    | 19.8-0.8 | 34.9                   | 88.9                   | 3.0                    | 1.08                  | 30.7                   | 4.60                               | 430                  |

|             |          |       |      |      |          |      |       |     |      |      |       |      |
|-------------|----------|-------|------|------|----------|------|-------|-----|------|------|-------|------|
| 7,00125E+11 | CG127/38 | 130.2 | 75.0 | 38.9 | 19.8-0.8 | 34.9 | 88.9  | 3.0 | 1.62 | 30.7 | 6.90  | 630  |
| 7,00125E+11 | CG127/51 | 130.2 | 75.0 | 51.6 | 19.8-0.8 | 34.9 | 88.9  | 3.0 | 2.16 | 30.7 | 9.23  | 800  |
| 7,00125E+11 | CG127/70 | 130.2 | 75.0 | 71.4 | 19.8-0.8 | 34.9 | 88.9  | 3.0 | 2.97 | 30.7 | 12.70 | 1090 |
| 7,00125E+11 | CG165/32 | 169.9 | 97.2 | 32.5 | 26.2-0.8 | 44.4 | 114.3 | 3.0 | 2.36 | 40.2 | 7.68  | 1060 |
| 7,00125E+11 | CG165/51 | 169.9 | 97.2 | 51.5 | 26.2-0.8 | 44.4 | 114.3 | 3.0 | 3.77 | 40.2 | 12.30 | 1620 |